

SPECIFICATIONS

Agera[®] Patent Pending

MEASUREMENT

Measurement Principle:	Dual-beam Reflectance Spectrophotometer
Geometry:	0°/45°c (circumferential) ASTM E1164
Measurement Method:	Port up or Port forward
Read Time:	< 3 sec.
Gloss:	60°
Image Capture:	High-resolution, D65 illuminated, 45°/0° image viewing, image capture and image recall with RGB histogram display for image analysis
Area Measured:	Color: XL - 51 mm (2 in), L - 25.4 mm (1 in), M - 16.9 mm (5/8 in) Gloss: Ø8 mm

TECHNICAL

Illumination Range:	360 nm - 700 nm
Detection Range:	400 nm - 700 nm
Specular Component:	Excluded
Spectral Resolution:	< 3 nm
Effective Bandwidth:	10 nm equivalent triangular
Reporting Interval:	10 nm
Photometric Range:	0 to 150 %
UV Control:	UV Included and UV Excluded with automated comparative data viewing and reporting. Factory calibrated with user option to calibrate to their specific fluorescent standard.
Light Source:	Full spectrum, balanced LED array
LED Life:	5 years typical
Spectrophotometer:	Sealed optics; 256-element diode array; high resolution concave holographic grating

PERFORMANCE

Reproducibility:	Color: $\Delta E_{2000} < 0.15$ CIE L*a*b* (Avg) on CCSII (CERAM) Tile Set Gloss: 0 - 100 GU: 0-20 GU ± 0.5 20-100 GU ± 1.0
Repeatability:	Color: $\Delta E_{2000} < 0.03$ CIE L*a*b* (Max) on white tile Gloss: 0 - 100 GU: ≤ 0.1 GU

QUALITY CONTROL SOFTWARE

ON-BOARD EASYMATCH ESSENTIALS COLOR QUALITY CONTROL SOFTWARE

Data Views:	EZ View, Color Data Table, Color Difference Data, Lab Color Plot, Spectral Data, Spectral Plot, Trend Plot
Other Features:	Pass/Fail color indication, time and date stamp, auto-naming, auto-saving, data backup and recovery
Indices and Metrics:	E313 Whiteness Index, Tint, E313 Yellowness Index, D1925 Yellowness Index, Y Brightness, Z%, 457 nm Brightness, Baking Contrast Units, HCCI, SCAA, ASTM E1349, Gloss: ASTM D523, ASTM D2457, ISO 2813, ISO 7668, JIS 28741
Color Scales:	CIE L*a*b*, Hunter Lab, CIE L*C*h, CIE Yxy, CIE XYZ
Color Difference Scales:	$\Delta L^*a^*b^*$, ΔLab , ΔL^*C^*h , ΔYxy , ΔXYZ
Color Difference Indices:	ΔE^* , ΔE , ΔC^* , ΔE CMC, ΔE 2000
Data Storage:	8 GB (> 1 million data records with images)
Illuminants:	A, C, D50, D55, D65, D75, F02, F07, F11
Observers:	2° and 10°
Languages:	English (other languages available soon)
External PC Software:	Compatible with HunterLab EasyMatch QC and EasyMatch QC-Electronic Records Quality Control Software

COMMUNICATIONS I/O

USB OTG:	Connectivity to printer, keyboard, mouse
Front Panel USB:	2.0 bidirectional, data export/import via thumb drive
Ethernet RJ45:	Print directly to standalone or network printers Email directly from the instrument Stream data to LIMS and SPC systems
Wi-Fi:	Available
Bluetooth:	Available
External Inputs:	Remote Footswitch or similar closed contact switching device
Remote Access Support:	Enabled via internet-based support tool

PHYSICAL / ELECTRICAL

Sensor Dimensions:	Height: 28 cm (11 in) Width: 22 cm (8.75 in) Depth: 31 cm (12.25 in) Weight: 6.35 kg (14 lb)
Display:	Capacitive touch screen, high-resolution color, 17.8 cm (7 in), 1280 x 800
Power:	Input: 100 to 240 VAC, 47 to 63 Hz to universal power supply @ 24 VDC (3.75A 90W)
Operating Environment:	4° to 38° C (40° to 100° F), 10 % to 85 % RH, noncondensing
Storage Environment:	-20° to 65° C (-5° to 150° F), 10 % to 90 % RH, noncondensing
System Components:	<ul style="list-style-type: none">• Agera sensor• XL - 51 mm (2 in), L - 25.4 mm (1 in), M 16.9 mm (5/8 in) port plates• Calibrated white tile (NIST Certificate of Traceability)• Calibrated black glass standard used for both color and gloss standardization (ASTM D523, ISO 2813 Certificates of Traceability)• Green diagnostic file• 100V - 240V universal power supply• Agera Quick Start Guide• Agera User's Guide on CD

For more information, please contact HunterLab at 703-471-6870, sales@hunterlab.com or visit www.hunterlab.com